

## JHM USA 101

Magnetic Base Drills up to 1 1/2 / 2 3/8 (38/60  $\,$ 

mm)

Part Number: 7 272 52 61 12 4



### For dimensionally-accurate drilling on the construction site.

Uniform-torque motor for demanding core drilling.

High concentricity and reliable core ejection due to special bore spindle guides.

Solid, massive construction in die-cast aluminum for work under difficult conditions. Integrated cooling tank.

Internal motor cable routing.

Accessory handle for easy carrying of tool.

Hand feed wheel can be mounted on either side.



# JHM USA 101

Magnetic Base Drills up to 1 1/2 / 2 3/8 (38/60 mm)

Part Number: 7 272 52 61 12 4

#### Technical data

| HSS core bit max. dia.          | 1 1/2 in      |
|---------------------------------|---------------|
| Core drill, max. drilling depth | 2 in          |
| Power consumption               | 1,050 Watts   |
| Power output                    | 530 Watts     |
| 1st gear                        | 480 rpm       |
| 1st gear                        | 330 rpm       |
| Core bit holder                 | 3/4 in Weldon |
| Stroke                          | 2 9/16 in     |
| Magnetic holding force          | 2,000 lbs     |
| Magnetic base sizes             | 6 5/16 x 4 in |
| Cable with plug                 | 12 1/2 ft     |
| Weight according to EPTA        | 31.7 lbs      |

### Price includes:

| 1 case            |
|-------------------|
| 1 coolant tank    |
| 1 safety strap    |
| 1 chip hook       |
| 4 centering pins  |
| 1 Allen key 5 mm  |
| 1 touch guard     |
| 1 Carrying handle |